




CX.500



- ✓ Modular brake
- ✓ Long life span
- ✓ Constant and precise torque control
- ✓ Minimum maintenance
- ✓ High heat dissipation
- ✓ Compact size
- ✓ Respect for the environment and operator's health




Since more than 40 years the Combiflex pneumatic brake has been representing the reference brake for the converting industry, today it's the best seller brake in the world.

The experience gained during years, thousands of applications, the constant research into materials and the studies carried out on brakes performance, have allowed us to increase our know how and to continually improve our product.

All our Combiflex brakes are equipped with asbestos free pads to guarantee respect for the working environment and the operator's health; moreover, they are equipped with a single fan and a turbine disc that convey the air flow in the crucial zone of the brake increasing the life span, the heat dissipation and reducing the maintenance.

Combiflex is a modular brake, it means that we can provide it with a number of calipers required by the application; moreover, the distributors of each caliper can always be accessed in order to select the most suitable number of calipers for the regulation.

Combiflex brake that guarantees long life span of the pads, constant and precise torque control, high heat dissipation and compact size.



 N. of calipers
 48 Torque in Nm relating n. of calipers

TECHNICAL CHARACTERISTICS

Torque max 1 caliper	330 Nm
Torque min 1 caliper	3,3 Nm
Pressure min / max	0,3/6 bar
Max disc rpm	1200 rpm
Total weight	53 kg
Disc inertia	0,66 Kgm ²
Heat dissipation without fan	23,5 kW
Heat dissipation with 110V/220V fan	12,6 kW

*Data are subject to technical change without notice

** Torque values relate to dynamic slipping